

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
18 August 2005 (18.08.2005)

PCT

(10) International Publication Number
WO 2005/075161 A1

(51) International Patent Classification⁷: **B26B 21/22**,
21/40

(21) International Application Number:
PCT/IB2005/050310

(22) International Filing Date: 26 January 2005 (26.01.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
04100436.7 5 February 2004 (05.02.2004) EP

(71) Applicant (for all designated States except US): **KONINKLIJKE PHILIPS ELECTRONICS N.V.** [NL/NL];
Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **VAN EIBERGEN SANTHAGENS, Robert, A.** [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). **BRADA, Ype. B.** [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven

(NL). **WESTERHOF, Willem, A.** [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). **AKKERMAN, Hette** [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).


(74) Agents: **WOLFS, Marc, J., M.** et al.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,

[Continued on next page]

(54) Title: A SHAVING HEAD HAVING A BLADE SUPPORTING MEMBER WITH REDUCED CROSS-SECTIONAL AREA



(57) Abstract: The invention relates to a shaving head (5) comprising at least two bladeshaped cutting members (7, 7', 7'') each having a straight cutting edge (9, 9', 9'') extending parallel to a longitudinal direction (Y) of the shaving head. Each cutting member is supported in a cartridge (11) of the shaving head by means of a supporting member (17) which supports the respective cutting member in a supported area (23) on the respective cutting member. Said supported area extends over a predetermined distance (D) perpendicular to the longitudinal direction. Each supporting member has a first portion (25) in contact with the supported area at a location remote from the cutting edge of the respective cutting member and a second portion (27) in contact with the supported area at a location near the cutting edge of the respective cutting member. The first portion has a basic cross-sectional area, seen perpendicularly to the longitudinal direction, and the second portion has a reduced cross-sectional area. According to the invention, the second portion (27) of the supporting member (17) of at least one of the cutting members (7, 7', 7'') extends over at least half of said predetermined distance (D). In this manner, the free space between two adjacent cutting members is considerably increased. As a result, the rinsability of the shaving head is improved, so that the risk of shaving debris accumulation between two adjacent cutting members is reduced.



WO 2005/075161 A1



SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations* AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ,

NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

Published:

- *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

A shaving head having a blade supporting member with reduced cross-sectional area

The invention relates to a shaving head comprising at least two blade-shaped cutting members each having a straight cutting edge extending parallel to a longitudinal direction of the shaving head, each cutting member being supported in a cartridge of the shaving head by means of a supporting member supporting the respective cutting member in
5 a supported area on the respective cutting member, said supported area extending over a predetermined distance perpendicular to the longitudinal direction, and each supporting member having a first portion in contact with said supported area remote from the cutting edge of the respective cutting member and a second portion in contact with said supported area near the cutting edge of the respective cutting member, said first portion having a basic
10 cross-sectional area, seen perpendicularly to the longitudinal direction, and said second portion having a reduced cross-sectional area.

The invention also relates to a shaving device having a grip and a shaving head releasably mounted to the grip.

15

A shaving head and a shaving device of the kinds mentioned in the opening paragraphs are known from US 6,243,951 B1. The known shaving head comprises three blade-shaped cutting members or cutting blades having parallel cutting edges. The supporting members, by means of which the cutting blades are supported in the cartridge of the shaving
20 head, each comprise a longitudinally extending upright beam portion from the upper edge of which extends a forwardly and upwardly inclined blade platform against the upper surface of which the respective cutting blade is fixed. The blade platform is provided with a plurality of uniformly spaced apart comb elements or teeth, which extend perpendicularly to the cutting edge of the respective cutting blade and project forward relative to the cutting edge. The
25 projecting teeth have a guiding effect influencing the shaving head to move over the skin in a direction perpendicularly to the cutting edges of the cutting blades, as a result of which the safety and comfort of the shaving head are enhanced. The base portions of the teeth are in contact with a relatively small portion of the supported area in which the supporting member supports the respective cutting blade. Accordingly, said base portions constitute said second

portion of the supporting member, which has a reduced cross-sectional area relative to the basic cross-sectional area of the first portion of the supporting member as a result of the indentations formed between the teeth.

5 A disadvantage of the known shaving head and shaving device is that during use shaving debris accumulates in the relatively narrow spaces between the blade-shaped cutting members. Because of said relatively narrow spaces, the shaving head is badly rinsable, so that it is difficult or even impossible to clean the shaving head after use. As a result of said accumulation of shaving debris, the shaving performance and shaving comfort of the shaving head are affected.

10

It is an object of the invention to provide a shaving head and a shaving device of the kinds mentioned in the opening paragraphs which are better rinsable, so that the risk of shaving debris accumulation between the blade-shaped cutting members is reduced.

15 In order to achieve this object a shaving head in accordance with the invention is characterized in that the second portion of the supporting member of at least one of the cutting members extends over at least half of said predetermined distance.

In order to achieve this object a shaving device in accordance with the invention is characterized in that the shaving head used therein is a shaving head in
20 accordance with the invention.

The supporting member of said at least one of the cutting members is present in the space between said at least one of the cutting members and the cutting member which precedes said at least one of the cutting members seen in the cutting direction. Since the second portion of said supporting member having the reduced cross-sectional area extends
25 over at least half of the predetermined distance over which, seen perpendicularly to the longitudinal direction, the supporting member supports the cutting member, the free space between said cutting members is considerably increased. As a result, the space between said cutting members is better rinsable, so that shaving debris accumulated in said space during use can be better removed by rinsing the shaving head after use. Alternatively, the blade-
30 shaped cutting members and the cutting edges can be arranged in the cartridge at smaller mutual distances without inadmissibly affecting the rinsability of the shaving head. As a result of said smaller mutual distances the shaving comfort of the shaving head is increased and the risk of skin irritation and skin damage is reduced.

A particular embodiment of a shaving head in accordance with the invention is characterized in that the second portion of the supporting member of each cutting member extends over at least half of said predetermined distance. In this embodiment, identical supporting members are used for the cutting members, so that the structure and
5 manufacturing process of the shaving head are simplified.

A particular embodiment of a shaving head in accordance with the invention is characterized in that the second portion is a wedge-shaped portion. The wedge-shaped portion provides a gradual and smooth contour of the free space between the cutting members, so that both the rinsability of said space is further improved and the risk of
10 accumulation of shaving debris in said space during use is reduced.

A particular embodiment of a shaving head in accordance with the invention is characterized in that the second portion is a toothed portion. In this embodiment, an improved rinsability of the space between the cutting members is achieved in particular as a result of an improved rinsability of the free portions of said space present between the individual teeth of
15 the toothed portion.

A further embodiment of a shaving head in accordance with the invention is characterized in that the toothed portion comprises wedge-shaped teeth. The wedge shaped teeth further improve the rinsability of a shaving head comprising supporting members with toothed portions.
20

Embodiments of a shaving head and a shaving device in accordance with the invention will be described in detail hereafter with reference to the Figures, in which:

Fig. 1 schematically shows a shaving device in accordance with the invention which is provided with a first embodiment of a shaving head in accordance with the invention;
25

Fig. 2 schematically shows a cross-section along the line II-II in Fig. 1;

Fig. 3 shows three cutting members and three supporting members of a second embodiment of a shaving head in accordance with the invention; and

30 Fig. 4 shows three cutting members and three supporting members of a third embodiment of a shaving head in accordance with the invention.

Figure 1 schematically shows a shaving device 1 in accordance with the invention. The shaving device 1 comprises a grip 3 and a first embodiment of a disposable shaving head 5 in accordance with the invention. The shaving head 5 is releasably mounted to the grip 3 by means of mechanical coupling means which are not visible in Figure 1.

5 In the embodiment shown, the shaving head 5 comprises three blade-shaped cutting members 7, 7', 7'' which are each provided with a straight cutting edge 9, 9', 9''. The cutting edges 9, 9', 9'' extend parallel to a longitudinal direction Y of the shaving head 5 and define a cutting or shaving direction X of the shaving head 5, which is directed perpendicularly to the longitudinal direction Y. The cutting members 7, 7', 7'' are supported
10 in a cartridge 11 of the shaving head 5 in a manner to be described in detail hereafter. The cartridge 11 further carries a profiled skin stretching element 13, which precedes the cutting members 7, 7', 7'' seen in the cutting direction X, and a skin lubricating element 15, which follows the cutting members 7, 7', 7'' seen in the cutting direction X. The skin stretching element 13 and the skin lubricating element 15 together define a skin contact surface via
15 which the shaving head 5 abuts against the skin during use of the shaving device 1.

As shown in Figure 2, the cutting members 7, 7', 7'' are each supported in the cartridge 11 of the shaving head 5 by means of a supporting member 17. In the first embodiment of the shaving head 5 shown in Figure 2, the supporting members 17 are identical and extend parallel to the longitudinal direction Y over substantially the complete
20 length of the cutting members 7, 7', 7'', the supporting members 17 having an identical cross-section in every imaginary plane extending perpendicularly to the longitudinal direction Y. Each supporting member 17 has a base portion 19, which is connected to the cartridge 11 and extends transversely relative to the respective cutting member 7, 7', 7'' it supports, and a supporting platform 21, which is inclined relative to the base portion 19 and to which the
25 respective cutting member 7, 7', 7'' is attached. As shown in Figure 2, each supporting member 17 supports the respective cutting member 7, 7', 7'' in a supported area 23 on the lower side of the respective cutting member 7, 7', 7'', said supported area 23 extending over a predetermined distance D in a direction perpendicular to the longitudinal direction Y and, in the embodiment shown, extending over substantially the complete length of the respective
30 cutting member 7, 7', 7'' seen in the longitudinal direction Y.

As shown in Figure 2, the supporting platform 21 of each supporting member 17 has a first portion 25, via which the supporting member 17 is in contact with the supported area 23 of the respective cutting member 7, 7', 7'' at a location remote from the cutting edge 9, 9', 9'' of the respective cutting member 7, 7', 7'', and a second portion 27, via which the

supporting member 17 is in contact with the supported area 23 of the respective cutting member 7, 7', 7'' at a location close to the cutting edge 9, 9', 9'' of the respective cutting member 7, 7', 7''. The first portion 25 has a uniform thickness t . As a result, seen in a direction perpendicular to the longitudinal direction Y, the first portion 25 has a uniform
5 rectangular cross-section with a basic cross-sectional area $t \cdot L$, wherein L is the length of the supporting member 17 in the longitudinal direction Y. In the first embodiment of the shaving head 5, the second portion 27 has a wedge-shaped cross-section seen in an imaginary plane extending perpendicularly to the longitudinal direction Y. Accordingly, seen in a direction perpendicular to the longitudinal direction Y, the second portion 27 has a rectangular cross-
10 section which gradually decreases from the first portion 25 towards the cutting edge 9, 9', 9'' and which accordingly has a reduced cross-sectional area relative to the basic cross-sectional area of the first portion 25.

As shown in Figure 2, the second wedge-shaped portion 27 of each supporting member 17 extends over at least half of the predetermined distance D over which the
15 supported area 23 of the respective cutting member 7, 7', 7'' extends in a direction perpendicular to the longitudinal direction Y. In the embodiment shown in Figure 2 the second wedge-shaped portion 27 extends over approximately 80% of the distance D . Accordingly, in this embodiment the first portion 25 of each supporting member 17 extends over only approximately 20% of the distance D . As a result, seen in a direction perpendicular
20 to the Y-direction, the supporting members 17 have a considerably reduced average cross-sectional area at locations where the supporting members 17 are present in the relatively narrow spaces between the cutting members 7, 7', 7''. As a result, the free space between the cutting members 7, 7', 7'' is considerably increased. As a result, the rinsability of the spaces between the cutting members 7, 7', 7'' is considerably improved, so that the risk of shaving
25 debris accumulation in said spaces during use is reduced and the shaving debris, which still accumulates in said spaces during use, can be relatively easily removed after use by rinsing the shaving head 5.

In the first embodiment of the shaving head 5 shown in Figure 2, the wedge-shaped second portions 27 of the supporting members provide a gradual and smooth contour
30 of the spaces between the cutting members 7, 7', 7''. Said gradual and smooth contour further improves the rinsability of said spaces and further reduces the risk of shaving debris accumulation in said spaces during use. In this embodiment, the supporting members 17 are mutually identical. This simplifies the structure and the manufacturing process of the shaving head 5.

It is further noted that the advantageous effect of a shaving head in accordance with the invention can also be exploited in a different manner. In particular, the mutual distances s (see Figure 2) between the cutting members 7, 7', 7'' can be reduced compared to a conventional shaving head like the shaving head known from US 6,243,951 B1. In this manner, a remarkable improvement of the rinsability can still be obtained. An important advantage of the reduced mutual distances s is that the risk of skin irritations and skin damages is reduced, so that the shaving comfort of the shaving head is strongly improved. By optimizing the mutual distances s , an optimum or other desired combination of the rinsability and the shaving comfort of the shaving head can be achieved.

Figure 3 shows three cutting members 31, 31', 31'' with parallel cutting edges 32, 32', 32'' and three supporting members 33 of a second embodiment of a shaving head in accordance with the invention. Apart from the supporting members 33 the second embodiment of the shaving head corresponds to the first embodiment of the shaving head 5. For this reason the other parts of the second embodiment of the shaving head are not shown in Figure 3 and will not be discussed hereafter.

As shown in Figure 3, the supporting members 33 are identical and extend parallel to the longitudinal direction Y over substantially the complete length of the cutting members 31, 31', 31''. Each supporting member 33 has a base portion 35, which is connected to the cartridge of the shaving head and extends transversely relative to the respective cutting member 31, 31', 31'' it supports, and a supporting platform 37, which is inclined relative to the base portion 35 and to which the respective cutting member 31, 31', 31'' is attached. Each supporting member 33 supports the respective cutting member 31, 31', 31'' in a supported area 39 on the upper side of the respective cutting member 31, 31', 31'' seen in the position of the cutting members 31, 31', 31'' shown in Figure 3, said supported area 39 extending over a predetermined distance D' in a direction perpendicular to the longitudinal direction Y and extending over substantially the complete length of the respective cutting member 31, 31', 31'' seen in the longitudinal direction Y .

The supporting platform 37 of each supporting member 33 has a first portion 41, via which the supporting member 33 is in contact with the supported area 39 of the respective cutting member 31, 31', 31'' at a location remote from the cutting edge 32, 32', 32'' of the respective cutting member 31, 31', 31'', and a second portion 43, via which the supporting member 33 is in contact with the supported area 39 of the respective cutting member 31, 31', 31'' at a location close to the cutting edge 32, 32', 32'' of the respective cutting member 31, 31', 31''. The first portion 41 has a uniform thickness t' . As a result, seen

in a direction perpendicular to the longitudinal direction Y, the first portion 41 has a uniform rectangular cross-section with a basic cross-sectional area $t' \cdot L'$, wherein L' is the length of the supporting member 33 in the longitudinal direction Y. In the second embodiment of the shaving head, the second portion 43 is a toothed portion having an array of teeth 45 with a uniform thickness t' identical to the thickness of the first portion 41 and with a constant mutual distance d . Accordingly, seen in a direction perpendicular to the longitudinal direction Y, the second portion 43 has a cross-section with a reduced cross-sectional area relative to the basic cross-sectional area of the first portion 41. For example, in an embodiment wherein the teeth 45 each have a width equal to the width of their mutual interspaces, said cross-sectional area of the second portion 43 will be approximately half of said cross-sectional area of the first portion 41.

As shown in Figure 3, the second toothed portion 43 of each supporting member 33 extends over at least half of the predetermined distance D' over which the supported area 39 of the respective cutting member 31, 31', 31'' extends in a direction perpendicular to the longitudinal direction Y. In the embodiment shown in Figure 3 the second toothed portion 43 extends over approximately 70% of the distance D' . Accordingly, in this embodiment the first portion 41 of each supporting member 33 extends over only approximately 30% of the distance D' . As a result, seen in a direction perpendicular to the Y-direction, the supporting members 33 have a considerably reduced average cross-sectional area at locations where the supporting members 33 are present in the relatively narrow spaces between the cutting members 31, 31', 31''. As a result, like in the first embodiment of the shaving head 5 described here before, the rinsability of the second embodiment of the shaving head is considerably improved, and the risk of shaving debris accumulation in the spaces between the cutting members 31, 31', 31'' is reduced. In the second embodiment, an improved rinsability of the spaces between the cutting members 31, 31', 31'' is achieved in particular as a result of an improved rinsability of the portions of said spaces which are present between the individual teeth 45 of the toothed portion 43.

Figure 4 shows three cutting members 51, 51', 51'' with parallel cutting edges 52, 52', 52'' and three supporting members 53 of a third embodiment of a shaving head in accordance with the invention. Apart from the supporting members 53 the third embodiment of the shaving head corresponds to the first embodiment of the shaving head 5. For this reason the other parts of the third embodiment of the shaving head are not shown in Figure 4 and will not be discussed hereafter. In Figure 4, parts of the third embodiment of the shaving

head which correspond to parts of the second embodiment of the shaving head described here before are indicated by corresponding reference numbers.

As shown in Figure 4, the supporting members 53 in the third embodiment of the shaving head mainly differ from the supporting members 33 in the second embodiment of the shaving head in that the teeth 45' of the second toothed portions 43' of the supporting members 53 are wedge-shaped. The result of the wedge-shape of the teeth 45' is that the rinsability of the third embodiment of the shaving head is further improved, and the risk of shaving debris accumulation in the spaces between the cutting members 51, 51', 51" is further reduced.

It is noted that in each embodiment of a shaving head in accordance with the invention described here before, the three supporting members 17, 33, 53 are mutually identical. In this manner the shaving head has a simple structure, and the free space between each pair of adjacent cutting members is increased. The invention generally covers embodiments in which the free space between at least one pair of adjacent cutting members is increased. For this reason, in each embodiment of a shaving head in accordance with the invention at least one of the cutting members has a supporting member with a second portion with a reduced cross sectional area extending over at least half of the predetermined distance over which the supporting member is in contact with the supported area on the cutting member. The supporting member of the cutting member, which is arranged in front, is not present in a space between two adjacent cutting members and, accordingly, does not necessarily need to have a second portion with a reduced cross-sectional area in order to provide improved rinsability of the shaving head.

It is further noted that the invention also covers embodiments of a shaving head having a different number of cutting members, for example two or four cutting members.

It is finally noted that the invention also covers embodiments in which the supporting members do not support the cutting members over their complete length seen in the longitudinal direction Y. A shaving head may, for example, comprise a number of supporting members for each cutting member arranged at regular mutual intervals seen in the longitudinal direction Y. In such an alternative embodiment, the invention improves at least the rinsability of the shaving head at locations between the cutting members close to the supporting members.

CLAIMS:

1. A shaving head comprising at least two blade-shaped cutting members each having a straight cutting edge extending parallel to a longitudinal direction of the shaving head, each cutting member being supported in a cartridge of the shaving head by means of a supporting member supporting the respective cutting member in a supported area on the
5 respective cutting member, said supported area extending over a predetermined distance perpendicular to the longitudinal direction, and each supporting member having a first portion in contact with said supported area remote from the cutting edge of the respective cutting member and a second portion in contact with said supported area near the cutting edge of the respective cutting member, said first portion having a basic cross-sectional area,
10 seen perpendicularly to the longitudinal direction, and said second portion having a reduced cross-sectional area, characterized in that the second portion of the supporting member of at least one of the cutting members extends over at least half of said predetermined distance.
2. A shaving head as claimed in claim 1, characterized in that the second portion
15 of the supporting member of each cutting member extends over at least half of said predetermined distance.
3. A shaving head as claimed in claim 1, characterized in that the second portion
20 is a wedge-shaped portion.
4. A shaving head as claimed in claim 1, characterized in that the second portion is a toothed portion.
5. A shaving head as claimed in claim 4, characterized in that the toothed portion
25 comprises wedge-shaped teeth.
6. A shaving device having a grip and a shaving head releasably mounted to the grip, characterized in that the shaving head is a shaving head as claimed in claim 1, 2, 3, 4, or 5.

1/4




FIG. 1

2/4




FIG. 2




FIG. 4

INTERNATIONAL SEARCH REPORT

 Int lional Application No
 PCT/IB2005/050310

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 B26B21/22 B26B21/40

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B26B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 01/39937 A (KONINKLIJKE PHILIPS ELECTRONICS N.V) 7 June 2001 (2001-06-07) page 5, lines 9-28; figures 2,3 -----	1,2,4,6
X	US 4 492 024 A (JACOBSON ET AL) 8 January 1985 (1985-01-08) column 3, lines 24-28; figures 1,5 -----	1,2,6
P,X	WO 2004/069495 A (EVEREADY BATTERY COMPANY, INC) 19 August 2004 (2004-08-19) page 4, line 16 - page 5, line 33; figures 1,2 -----	1,4,6
A	EP 0 858 869 A (WARNER-LAMBERT COMPANY) 19 August 1998 (1998-08-19) column 4, lines 20-27; figures 1,3 -----	1



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

° Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- * & * document member of the same patent family

Date of the actual completion of the international search

9 May 2005

Date of mailing of the international search report

19/05/2005

Name and mailing address of the ISA

 European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Rattenberger, B

INTERNATIONAL SEARCH REPORT

Inventor's Application No
PCT/IB2005/050310

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 0139937	A	07-06-2001	AT 235354 T CN 1337899 A DE 60001815 D1 DE 60001815 T2 WO 0139937 A1 EP 1163089 A1 ES 2192546 T3 JP 2003515401 T US 6671961 B1 US 2004216310 A1	15-04-2003 27-02-2002 30-04-2003 04-12-2003 07-06-2001 19-12-2001 16-10-2003 07-05-2003 06-01-2004 04-11-2004
US 4492024	A	08-01-1985	CA 1209327 A1 US 4498235 A US 4621424 A US 4573266 A	12-08-1986 12-02-1985 11-11-1986 04-03-1986
WO 2004069495	A	19-08-2004	US 2004255467 A1 WO 2004069495 A1	23-12-2004 19-08-2004
EP 0858869	A	19-08-1998	AU 748642 B2 AU 4764697 A CA 2223161 A1 DE 69808815 D1 DE 69808815 T2 EP 0858869 A1 JP 10286383 A	06-06-2002 23-07-1998 17-07-1998 28-11-2002 24-12-2003 19-08-1998 27-10-1998

PUB-NO: WO2005075161A1
DOCUMENT-IDENTIFIER: WO 2005075161 A1
TITLE: A SHAVING HEAD HAVING A
BLADE SUPPORTING MEMBER WITH
REDUCED CROSS-SECTIONAL AREA
PUBN-DATE: August 18, 2005

INVENTOR--INFORMATION:

NAME	COUNTRY
VAN, EIBERGEN SANTHAGENS ROBERT	NL
BRADA, YPE B	NL
WESTERHOF, WILLEM A	NL
AKKERMAN, HETTE	NL

ASSIGNEE--INFORMATION:

NAME	COUNTRY
KONINKL PHILIPS ELECTRONICS NV	NL
VAN EIBERGEN SANTHAGENS ROBERT	NL
BRADA YPE B	NL
WESTERHOF WILLEM A	NL
AKKERMAN HETTE	NL

APPL-NO: IB2005050310
APPL-DATE: January 26, 2005

PRIORITY-DATA: EP04100436A (February 5, 2004)

INT-CL (IPC): B26B021/22 , B26B021/40

EUR-CL (EPC): B26B021/22 , B26B021/22 ,
B26B021/40

ABSTRACT:

CHG DATE=20050830 STATUS=O>The invention relates to a shaving head (5) comprising at least two blade-shaped cutting members (7, 7', 7'') each having a straight cutting edge (9, 9', 9'') extending parallel to a longitudinal direction (Y) of the shaving head. Each cutting member is supported in a cartridge (11) of the shaving head by means of a supporting member (17) which supports the respective cutting member in a supported area (23) on the respective cutting member. Said supported area extends over a predetermined distance (D) perpendicular to the longitudinal direction. Each supporting member has a first portion (25) in contact with the supported area at a location remote from the cutting edge of the respective cutting member and a second portion (27) in contact with the supported area at a location near the cutting edge of the respective cutting member. The first portion has a basic cross-sectional area, seen perpendicularly to the longitudinal direction, and the second portion has a reduced cross-sectional area. According to the invention, the second portion (27) of the supporting member (17) of at least one of the cutting members (7, 7', 7'') extends over at least half of said predetermined distance (D). In this manner, the free space between two adjacent cutting members is considerably increased. As a result, the rinsability of the shaving head is improved, so that the risk of shaving debris accumulation between two adjacent cutting members

is reduced.